

AddressRight™ DA³⁰⁰ Addressing Printer

» Create a look that gets your mail noticed and opened

Create and print professional looking addresses directly onto postcards, envelopes and a variety of other mail pieces.

» Fast, efficient, productive

Address DL envelopes at speeds of up to 4,200 per hour (3 lines, no graphics). Handles a variety of sizes by automatically feeding materials from 76 x 127mm up to 324 x 343mm and up to 1.6mm thick.

The optional Conveyor/Stacker increases productivity even further.

» Saves time, labour and materials

Eliminate the expense of applying labels, and speed up productivity by nearly two hours per 1,000 envelopes.

» Easy-to-use

An advanced feeder design and sensitive thickness settings make it simple to adjust for materials of various sizes.

Clear, plain text prompts on the control panel, guide the user. The printer can be used by anybody in the office.

The quick-change ink cartridge snaps in and out without any fuss or mess.

» Save money by maximising postal discounts

By using our optional FlexMail® software, you can earn postal discounts that will reduce your postage costs significantly on volume mailings.

FlexMail® also offers the options of de-duplication and address validation for your databases, again offering significant savings by not mailing to duplicated or non-existent addresses.



AddressRight™ DA³⁰⁰

DA³⁰⁰ Specifications



- » **Maximum speed** Up to 4,200 items per hour (at 150dpi)
- » **Print resolution** Up to 600 dpi
- » **Media sizes (mm)**
 - Min 76 x 127
 - Max 324 x 343
 - Max Thickness 1.6mm

Note: We only recommend portrait printing of A4/C4 materials on this model

- » **Dimensions (mm)**
 - Height 373
 - Width 412
 - Depth 551
 - Weight 18.2kg
- » **Internal Fonts** 12pt only
Courier, Sans Serif, Roman
- » **Lines per page** Unlimited
- » **Printable Width** 238mm
- » **Noise** <65dBA
- » **Conveyor Stacker** Optional
- » **Electrical** 220/240Vac, 50Hz
- » **Operation** Requires an IBM compatible PC running Microsoft Windows™ 3.1 or above
- » **Input Stack** 200 DL envelopes (unstuffed)
- » **Output Stack** 150 DL envelopes (unstuffed) in tray, or continuous with optional Conveyor Stacker
- » **Emulation** Hewlett Packard PCL5 subset
- » **Interfaces** Centronics parallel and RS232 Serial
- » **Barcodes** Postnet built in, others via download
- » **Display Languages** UK English, French, German, Italian, Spanish, Dutch
- » **Printable Character Sets** UK English, French, German, Italian, Danish/Norwegian, Swedish/Finnish

Pitney Bowes Danmark

Telefon 70 221 223 • Fax 70 221 243
www.pitneybowes.dk

© 2003 Pitney Bowes Ltd. All rights reserved.

Specifications are subject to change without notice. Performance may vary depending on exact job configuration and environmental conditions